

www.damcon.nl



Plantmachine met spitelement

Pflanzmaschinen mit Spatenmaschine

Tree planting machines with integrated digging machine

Planteuses avec bêche rotative

Type / Typ / Type / Type	PL - 30	PL - 40	PL - 75	PL - 90
Aanbouw / Anbau Fitted to / Montage	3 - P Cat I	3 - P Cat I-II	3 - P Cat II	3 - P Cat II
Aandrijving / Antrieb Drive / Commande	540 / 750 p/min	540 / 750 p/min	1000 p/min	1000 p/min
Sleufbreedte / Grabenbreite Groove width / Largeur de la rainure	30 cm	40 cm	75 cm	90 cm
Sleufdiepte / Grabentiepe Groove depth / Profondeur de la rainure	25 cm	30-35 cm	40 cm	50 cm
Tractor / Schlepper Tractor / Tracteur	30 kW	40 kW	90 kW	120 kW
Capaciteit p/d / Kapazität p/T Input trees p/d / Capacité p/j	3000 - 4000	3000 - 4000	500 - 1500	500 - 1500
Min. rijafstand / Min. Reiheabstand Min. row width / Distance min. entre les rangs	100 cm	125 cm	150 cm	200 cm
Max. stamomvang / Max. Umfang Max. tree girth / Tour max.	8 - 10 cm	18 - 20 cm	20 - 25 cm	25 - 30 cm
Gewicht / Gewicht Weight / Poids	425 kg	465 kg	1500 kg	2500 kg
Hydr. kluitenlift / Hydr. Ballenvorrichtung Hydr. rootball lift / Ascenseur hydr. de motte	-	-	Optie / Option	Optie / Option
Kluitendiameter / Ballendurchmesser Rootballdiameter / Diamètre de la motte	-	-	60 cm ø	90 cm ø

