

www.damcon.nl



Select bomenrooimachines

Select Baumrodemaschinen

Select tree lifting machines

Transplanters pour montage aux chargeurs

Type / Typ / Type / Type	2W-Select-40 KV	Select-40 KV	Select-50	Select-80
Aanbouw / Anbau Fitted to / Montage	2W	3-P	3-P	3-P
Ben. vermogen / Ben. Leistung Drive / Commande	15 kW	15 kW	30 kW	40 kW
Onderschudder / Unterrüttler Undershaker / Secoueur	-	-	St.	St.
Lengte / Länge Length / Longueur	195 cm	110 cm	150 cm	180 cm
Breedte / Breite über alles Width / Largeur	90 cm	90 cm	95 cm	105 cm
Gewicht / Gewicht Weight / Poids	675 kg	460 kg	485 kg	575 kg
Capaciteit p/u / Kapazität p/S Output trees p/h / Capacité p/h	80-120	80-120	80-120	80-120
Max. stamomvang / Max. Umfang Max. tree girth / Tour max.	16 -18 cm	16 -18 cm	20 - 25 cm	25 - 30 cm
Rooides vlak / Messer flach Blade flat / Lame plat	20 - 40 cm	25 - 40 cm	-	-
Rooides U / Messer U Blade U / Lame U	40 - 50 cm	40 - 50 cm	50 - 70 cm	80 - 100 cm

Standaard met een Damcon hydroklem-schudder / Standard mit einem Damcon Hydroklemm-Rüttler
 Standard with a Damcon hydroclamp-shaker / Le modèle standard est pourvu d'une pince de secouer
 Damcon à commande hydraulique

